



YOUR WORKING AT HEIGHT PARTNER

We call it 'Non-Powered, Powered Access.'

As part of the Eco range the EcoLift still harnesses the same Eco friendly revolutionary 'Patented Stored Power System' as the PecoLift but at 4.2 m offers almost a metre extra in working height.

With no batteries (to charge and look after) and no hydraulic oil, the EcoLift is truly an Eco friendly solution.

Typical applications and uses:

1st & 2nd Fix. Pipe Work, M & E. FM. Cleaning. Painting. Retail. Point of Sale. FM.

Key Features

- Intuitive to operate turn handle to elevate
- Patented* lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small footprint (1.28 x 700 mm)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

PUSH AROUND - Self Powered

Indoor Use

Working Height: 4.2 m

Applications: 1st & 2nd fix. Pipe Work, M&E. F.M. Cleaning. Painting. Point of Sale. Retail.







Specifications

WORKING DIMENSIONS

Maximum working height: Maximum platform height:

Basket dimensions: Working footprint:

Safe working load: Maximum manual force:

Maximum gradient for operation:

Maximum wind force: Maximum wheel force:

Sound pressure level:

4.20 m 2.20 m

850 mm (L) x 644 mm (W)

1.28 m x 700 mm

150 kg (1 person + tools)

200N 0 degrees

Internal use only, 0 (zero) mph

234 kg

Less than 70 Dba

Safety features

- 'Auto-lok' brake on elevation
- Elevates only when operated
- Lifting mechanism interlocked

CLOSED DIMENSIONS

Length: 1.28 m Width: 0.70 m Height: 1.94 m Weight: 305 kg

LIFT CYCLES Unlimited

