

YOUR WORKING AT HEIGHT PARTNER

Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.

Product description

- Continuous adjustment to the millimetre. Each individual stile of the ladder locks securely by the turn of a handle.
- Stile dimensions: 60 x 24 mm.
- Rungs and stiles made from aluminium extrusions.
- High strength, non-twist rung/stile connections.
- Replaceable two-component plastic end caps that attach securely to the stile and prevent the ladder from slipping.

Product features

Coating: natural
 Connection between stiles and rungs/stiles: flanged
 Load: max. 150 kg
 Material: aluminium
 Number of ladder sections: 2
 Product type: Flanged stepladder with rungs and extending stiles
 Tread depth: 30 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 265 mm

Product variants

Order number	Additional adjustment range on support section	Length excluding extension	Number of rungs	Number of rungs	Transport dimensions	Weight
41936	1.3 m	1.8 m	6	2 x 6	1.850 mm x 600 mm x 140 mm	12.5 kg
41938	1.85 m	2.35 m	8	2 x 8	2.410 mm x 650 mm x 140 mm	15.5 kg



Hints and special features

Ideal for applications in difficult terrain.

