

## **HLS Quick Up**

### YOUR WORKING AT HEIGHT PARTNER



### **QUICK UP**













# ADAPTED TO EACH PROJECT

- Its lightweight makes it suitable for the most fragile grounds
- Its compactness enables to go through doors and elevators
- Its stabilizers with rubber protect the floor surface

#### **EASY TO USE**

- > Quick set up by 1 person
- > Transportable on a trailer or a van
- 4 wheels for easy manual maneuvering

### BEST VALUE FOR MONEY

> Minimal maintenance





## **HLS Quick Up**

### YOUR WORKING AT HEIGHT PARTNER



#### PUSH-AROUND BOOMS

### **TECHNICAL DATA**

-	QUICK UP 7	QUICK UP 8	QUICK UP 9	QUICK UP 11	QUICK UP 12	QUICK UP 13	QUICK UP 14
Working height	6.7 m	8.1 m	9.5 m	10.8 m	12.3 m	13.7 m	14.3 m
G Platform height	4.7 m	6.1 m	7.5 m	8.8 m	10.3 m	11.7 m	12.3 m
Lift capacity	159 kg	159 kg	159 kg	159 kg	136 kg	136 kg	136 kg
Platform size	0.68 x 0.66 m						
<b>⑥</b> Length	1.22 m	1.28 m	1.28 m	1.34 m	1.4 m	1.47 m	1.42 m
Width	0.8 m						
A Height - stowed	1.78 m	1.98 m	2.8 m				
Width - stabilised	1.55 m	1.55 m	1.55 m	1.55 m	2.06 m	2.34 m	2.33 m
● Length - stabilised	1.75 m	1.75 m	1.75 m	1.75 m	2.26 m	2.7 m	2.58 m
①x③ Tilt bar	N/A	N/A	N/A	N/A	N/A	N/A	2.85 x 1.99 m
Energy (AC)	110 or 230 V						
Weight (AC)	315 kg	340 kg	360 kg	380 kg	415 kg	455 kg	515 kg
Energy (DC)	12 V						
Weight (DC)	357 kg	382 kg	402 kg	422 kg	457 kg	497 kg	557 kg

### **STANDARD EQUIPMENT**

- > Easy to use thanks push button controls
- > Emergency control
- > Manual platform lowering valve
- > Integrated forklift pockets
- > Lifting eye
- > Non marking wheels
- > Harness attachment point
- > Lights on control box to confirm stabilizers are set

#### **OPTIONS AND ACCESSORIES**

2 available versions: supply-power (AC) or battery (DC)

